

Tap water fingerprinting using convolutional neural network built from coffee-ring effect images



Xiaoyan Li
PhD
Candidate



Professor
Rebecca Lahr
Principal
Investigator



MICHIGAN STATE
UNIVERSITY

Aug 7, 2020

Xiaoyan Li, Rebecca H. Lahr

Research goal


1. Develop a new low-cost water fingerprinting method

- Water analysis usually requires different methods/instruments for each analyte class
- Few of the multiplex, fast, low-cost methods are sensitive, accurate, and precise enough for reliable tap water monitoring
- We are working to harness water fingerprints created using the coffee-ring effect for low-cost, multiplex water chemistry monitoring

2. Develop an algorithm (CNN model) to harness water fingerprints

- Water fingerprints are images
- Water fingerprints sensitive to water chemistry
- Current models are not strong enough to extract chemistry information from water fingerprints

MSU academic hall



To harness the Coffee Ring Effect



Dried Detroit water

Aluminum slide


Residual of
evaporated water

Ring pattern

Solid Separated by size (Wong 2011)



Evaporation




Tap Water Sample

Aluminum Substrate


Hu & Larson. *J. Phys. Chem. B* 2006, 110 (14), 7090-7094.

Simple setup to harness coffee ring effect


Step 1: Peel off plastic film and clean the slide surface




Step 2: Coffee ring effect brings particles to droplet edge




Step 3: Less soluble crystals formed first




Step 4: More soluble crystals formed later






Dropping sample droplet and take the picture




Water fingerprints created by coffee ring effect are unique for tap water from each city

MINIMALLY TREATED GROUNDWATER




REVERSE OSMOSIS

LIME SOFTENED




ION EXCHANGE




UNTREATED GROUNDWATER

UNTREATED GROUNDWATER




SURFACE WATER SOURCE

SURFACE WATER SOURCE – LAKE MICHIGAN



Li, X, A. Sanderson, S Allen, and R. Lahr. 2020 *The Analyst*, January.



Machine Learning techniques have been used to solve many complex problems

Different deep learning networks are used to analyze each different data type

Convolutional neural network

For image data, for example, medical image data, face recognition and object detection

Long short-term memory network

For series data, for example time series data, speech data, robot control, grammar learning

Recurrent neural networks

For series data, for example text data, speech data, machine translation

Generative adversarial network


For two networks contest with each other, for example, fashion, science, video games, Miscellaneous applications

Reinforcement learning

Along side of supervised learning and unsupervised learning, for example, AlphaGo


Convolutional neural network (CNN) have been used for image analysis in many different fields

Magnetic resonance images and Computerized tomography images




H. R. Roth, A. Farag, L. Lu, E. B. Turkbey and R. M. Summers, in Medical Imaging 2015: Image Processing, International Society for Optics and Photonics, 2015, vol. 9413, p. 94131G.

Molecular structure for toxicity prediction




Y. Matsuzaka and Y. Uesawa, Optimization of a Deep-Learning Method Based on the Classification of Images Generated by Parameterized Deep Snap a Novel Molecular-Image-Input Technique for Quantitative Structure–Activity Relationship (QSAR) Analysis, Front. Bioeng. Biotechnol., 2019, 7, 65.

Quantification of Analyte Concentration in the Single Molecule Regime




W. J. Thrift and R. Ragan, Quantification of Analyte Concentration in the Single Molecule Regime Using Convolutional Neural Networks, Anal. Chem., 2019, 91, 13337–13342.

Convolutional Neural Networks structure includes convolutional layers, max pooling layers and fully connected layers to take input images and extract features of interest



A. Krizhevsky, I. Sutskever and G. E. Hinton, in Proceedings of the 25th International Conference on Neural Information Processing Systems, vol. 1, pp. 1097–1105.


Convolutional layers work to extract nonlinear features by multiplying by the feature parameter matrix with image matrix



Convolutional layer illustration

<https://towardsdatascience.com/a-comprehensive-guide-to-convolutional-neural-networks-the-eli5-way-3bd2b1164a53>


Max pooling layers work to extract the most important information (features) from convolutional layers processed layers.



Max pooling illustration


<https://developers.google.com/machine-learning/practica/image-classification/convolutional-neural-networks>

Fully connected layers work to correlate image features with nonlinear activation function to reduce 2-D image to 1-D data




Fully connected layer

Parameters in the fully connected layers will be updated by backpropagation based on the target output



Activation Node


Used standard methods for analysis of water to measure chemistry and used for residue analysis



30 water collected across Michigan State
Instruments: ICP-OES, IC, pH meter, oven,
AA, conductivity meter
Time consumed: **around 3 month**



Samples were grouped based on their water chemistry using cluster analysis




Clustering method groups water samples based on their chemistry data

Is that possible to correlate water samples coffee ring effect pattern with chemistry data?


Water fingerprints created by coffee ring effect are unique for tap water from each city

MINIMALLY TREATED GROUNDWATER




REVERSE OSMOSIS

LIME SOFTENED




ION EXCHANGE




UNTREATED GROUNDWATER

UNTREATED GROUNDWATER




SURFACE WATER SOURCE

SURFACE WATER SOURCE – LAKE MICHIGAN




Li, X, A. Sanderson, S Allen, and R. Lahr. 2020 *The Analyst*, January.


Convolutional Neural Network model for water residue pattern recognition



Ten CNN models were created, and assigned the image to a group with similar water chemistry (cluster analysis) with an accuracy of $77 \pm 3 \%$




Classes with more images were more accurate.







Class	Waters included
1	Surface waters, RO, others (MSU residence hall, East Lansing)
2	Untreated well water with high TDS
3	Lime softened
4	Minimally treated groundwater, other (Williamston)
5	Untreated groundwater, some minimally treated
6	Well water with high TDS after ion exchange

Larger dataset needed to achieve higher accuracy


Images were analyzed using Matlab particle analysis and python image analysis



Li, X, A. Sanderson, S Allen, and R. Lahr. 2020 *The Analyst*, January.



Principal component analysis (PCA) aids in classification of samples into groups with similar ions



PCA method couldn't recognize nonlinear features so the classification result is not good enough


Oliveira et al., 2017. *International Conference on Digital Image Computing: Techniques and Applications*, 1–8.

PCA on particle measurement data


PCA on image files

Future Work: To build a CNN model to predict where elements deposit and use it to quantify the element

CaCl_2 , MgCl_2 , NaCl mixture




scanning electron microscope (SEM) image




SEM-EDS, elemental analysis map


Li, X, R. Lahr. Paper unpublished




Cl



Na



O



200um

Conclusion-Coffee ring effect with CNN model could monitor water components

- There is correlation between water samples coffee ring effect pattern and water chemistry

- Cluster analysis could classify water samples based on their chemistry data

- Principal component analysis on water sample residue patterns couldn't classify water samples well because data is non-linear

- CNN model could effectively recognize tap water residue patterns and classify water samples based on the patterns

Thank you!



Xiaoyan Li
PhD Student



Alyssa Sanderson
Undergraduate
Researcher



Selett Allen
Undergraduate
Researcher



Zoe Wilton
Undergraduate
Researcher

MICHIGAN STATE
UNIVERSITY

Xiaoyan Li lixiaoy5@msu.edu

